



DONGGUAN HAIXIANG ADHESIVE PRODUCTS CO., LTD

Factory address: No.5 1road jiaoli east area, zhongtang town,Dongguan City, Guangdong province, China

TEL: +86 769-21663116 FAX: +86 769-39022795 Website: <http://www.tapemanufacture.com/>

Double sided Haixiang VHB foam tape physical performance test sheet

No	Item	Unit	Test Standard	Test way	Technical Data	
1	appearance	\	our tape is per roll, tidy surface, uniform colour, two sides is tidy, not fold, and stain and so on defect.	visual test	\	
2	stripping	\	Don't allow glue to drop or move to the reverse side of release paper	GB-4850-1984	\	
3	Thickness	mm	1 ± 0.05	\	1	
4	Glue width	mm	≥ 800	\	800	
5	Initial tack	inside	Ball No. (#)	≥ 8	GB-4852-1984	8
		outside				10
6	Permanent adhesion	inside	H/25m	≥ 28	GB-4851-1998	\
		outside				\
7	180 peel strength	inside	N/25m	≥ 0.45	GB-2792-1988	0.5
		outside				0.45
8	pressure	15 psi (100KPa)				
9	duration	24 months				
10	Test condition	Temperature $23 \pm 2^{\circ}$ C relative temperature $65 \pm 5^{\circ}$ C				